



M07: UC^{FUTURE} Data Centre Cable For Raceways

Ø4.5 mm robust cable for data centres with 12 fibres



Eca
CPR

Application and installation

The intended application for this cable is internal connections inside data centres, where the cable is installed on "raceways" or other means where a robust cable is called for.

Fits multi fibre connectors such as the MPO® and MTP® connectors according to IEC 61754-7-1

Standards

EN 50173-5, IEC 60794-2-20, ISO/IEC 24764

Flame resistance

LSHF-FR (FRNC): IEC 60332-1-2; IEC 60754-1; IEC 60754-2; IEC 61034; Class E_{ca}

Options

As an option this cable is available with 2, 4, 8 and 10 fibres.

Construction

Fibre	12 primary coated fibres nominally 242 µm	
Fibre colours	According to TIA/EIA 598-C also in agreement with IEC 60304: Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink and aqua	
Strength member	Ultra high modulus Aramid yarns	
Inner sheath	FireRes® halogen free, flame resistant thermoplastic sheathing compound acc. to EN 50290-2-27, UV stabilised, 0.45 mm	
Reinforcement	Ultra high modulus Aramid yarns	
Outer sheath	Halogen free, flame resistant thermoplastic sheathing compound acc. to EN 50290-2-27, UV stabilised, 0.5 mm	
Sheath colours	Cable with BendBright ^{XS} SM fibres G.657.A2	Yellow, RAL 1018
	Cable with MaxCap-BB-OM3	Aqua, RAL 6027
	Cable with MaxCap-BB-OM4	Erika violet RAL 4003
	Cable with BendBright WideCap-OM5	Lime-Green

Physical properties

M07: UC^{FUTURE} Data Centre Cable For Raceways

Property	IEC 60794-1-21/22 method	Value
Fibre count	-	12
Nominal dimensions	-	Inner: $\varnothing 3.0$ mm +0.1 mm -0.2 mm Outer: $\varnothing 4.5$ mm +0.2 mm -0.2 mm
Nominal weight	-	20 kg/km
Tensile strength (dynamic)	E1	1000 N
Tensile strength (permanent)	E1	500 N
Compressive strength (crush)	E3	500N
Impact	E4	5 Nm, R= 12.5 mm
Torsion	E07	Pass
Kink	E10	No kink
Min. bending radius	E11	R = 20 mm
Temperature range	F12	According to IEC 60794-2-50 F12: -10°C to 70°C

Product codes – ordering information

Product code	Product description	Fibre count	Fibre type	Fibre data sheet
60029956	UC ^{FUTURE} FO LBP M07 LSHF-FR 12 OM3B AQ	12	MaxCap-BB-OM3	C31
60032671	UC ^{FUTURE} FO LBP M07 LSHF-FR 12 OM4B 4003	12	MaxCap-BB-OM4	C32
	UC ^{FUTURE} FO LBP M07 LSHF-FR 12 OM5B LG	12	WideCap-OM5	C39
60038485	UC ^{FUTURE} FO LBP M07 LSHF-FR 12 SM7B YL	12	BendBright ^{XS} G.657.A2	C24
	UC ^{FUTURE} FO LBP M07 LSHF-FR 12 SM7B.P YL	12	BendBright ^{XS} G.657.A2, tight geometry	C25
	UC ^{FUTURE} FO LBP M07 LSHF-FR 12 SM7A1.P YL	12	BendBright G.657.A1, tight geometry	C38

© PRYSMIAN GROUP 2017, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.